



Black Diamond Series Flood Light

- Rectangular shaped, simple appearance with classic black and white color match providing a comfortable vision
- Patented heat dissipation system guarantees steady performance and long lifespan.
- Narrow light angle, uniform light spots, wide illumination area.
- Projection angle adjustable according to different requirements, convenient and firm installation.



IP 65

Item No.	System Power (W)	#of LEDs	Lumen Output 5000K (lm)	CCT	Driver Efficiency	Dimension(mm)
FL1N1056	64	56	4700	5000±300K	>88%	L308×W320×H321
FL1N1070	78	70	5900	5000±300K	>90%	L356×W320×H321
FL1N1084	93	84	7100	5000±300K	>91%	L405×W320×H321
FL1N1098	108	98	8800	5000±300K	>91%	L453×W320×H321
FL1N1112	123	112	9400	5000±300K	>91%	L502×W320×H321
FL1N1126	139	126	10700	5000±300K	>91%	L550×W320×H321
FL1N1140	154	140	11800	5000±300K	>91%	L599×W320×H321
FL1N1154	169	154	13000	5000±300K	>91%	L647×W320×H321
FL1N1168	185	168	14200	5000±300K	>91%	L696×W320×H321

Ordering Information	FL1N	1112	S5	50	MB	V24	2	0
	1	2	3	4				
1 System Power	1056: 64W 1070: 78W	1084: 93W 1098: 108W	1112: 123W 1126: 139W	1140: 154W 1154: 169W	1168: 185W			
2 Light Distribution	S5			S7				
3 Color Temp	30: 3000±300K		40: 4000±300K		50: 5000±300K			
4 Input Voltage	V24: AC 100-240V			V27: AC 120-277V				

