


STREET LIGHT RL1E UFO SERIES



A2



PRODUCT CHARACTERISTICS:

1. Accurate light distribution design, high luminance, illuminance and uniformity, different roads applicable
2. Patented finned heat dissipation design, achieve optimum efficiency
3. Remote control system applicable, realize secondary energy saving
4. Streamline design concept, tadpole cosmetic shape, modern style

APPLICATION

Major road, local road, crossing, express way, rural road, industrial estate, national road,

<p>RL1E1112A255SGA2216</p>	<p>unit:mm</p>																										
<p>Installation sketch:</p> <p>pole</p>	<table border="1"> <tr> <td>Input Voltage</td> <td>AC100~277V</td> </tr> <tr> <td>Frequency Range</td> <td>50/60Hz</td> </tr> <tr> <td>System Consumption</td> <td>127W</td> </tr> <tr> <td>LED Initial Flux</td> <td>11250 lm</td> </tr> <tr> <td>Power Efficiency</td> <td>> 88%</td> </tr> <tr> <td>Power Factor</td> <td>> 0.95</td> </tr> <tr> <td>Luminaire Efficiency</td> <td>> 90%</td> </tr> <tr> <td>Color Temperature</td> <td>2700~5500K</td> </tr> <tr> <td>Color Rendering Index</td> <td>Ra > 75</td> </tr> <tr> <td>Operation Environment</td> <td>Temp.-40°C ~ +50°C, Humidity 10%~95%</td> </tr> <tr> <td>IP Rating</td> <td>IP 65</td> </tr> <tr> <td>Lifetime</td> <td>> 50000H</td> </tr> <tr> <td>Net Weight</td> <td>13Kg</td> </tr> </table>	Input Voltage	AC100~277V	Frequency Range	50/60Hz	System Consumption	127W	LED Initial Flux	11250 lm	Power Efficiency	> 88%	Power Factor	> 0.95	Luminaire Efficiency	> 90%	Color Temperature	2700~5500K	Color Rendering Index	Ra > 75	Operation Environment	Temp.-40°C ~ +50°C, Humidity 10%~95%	IP Rating	IP 65	Lifetime	> 50000H	Net Weight	13Kg
Input Voltage	AC100~277V																										
Frequency Range	50/60Hz																										
System Consumption	127W																										
LED Initial Flux	11250 lm																										
Power Efficiency	> 88%																										
Power Factor	> 0.95																										
Luminaire Efficiency	> 90%																										
Color Temperature	2700~5500K																										
Color Rendering Index	Ra > 75																										
Operation Environment	Temp.-40°C ~ +50°C, Humidity 10%~95%																										
IP Rating	IP 65																										
Lifetime	> 50000H																										
Net Weight	13Kg																										